

TEC LABEL PRINTER B-882

TEC LABEL PRINTER B-882

The TEC B-882 series is part of the new generation of TEC printers.

This 8.4" printer continues with the same features found on the field proven B-872 series:

- 1) Wide range of fonts and barcodes
- 2) Industrial strength steel case for harsh environments
- 3) LCD and LED operator displays
- 4) 300m ribbon.

With a 300 dpi edge type printhead and print speeds of up to 8 ips, TEC's superb print quality is maintained at a level expected from a leading printer manufacturer. To this incredible package TEC has added a new range of advanced features. Using the optional PCMCIA I/F board, more Logo's, Fonts and Format details can be stored on PCMCIA memory cards. With this board you can also implement network solutions using a PCMCIA Ethernet LAN Card (supporting FTP Client / Server, LPD) which when fitted offers Internet Web Printer Control. A new faster CPU (internal clock speed 60 MHz, external clock speed 30 MHz) improves the overall throughput, and coupled with the greater memory capacity (16 MB) provides a print length of up to 54 inches (1.364 m).

Other options include 20 Downloadable True Type Fonts, Swing Cutter, & Strip Module, giving the performance and flexibility needed to meet all your printing requirements.

B-882

Specification



Printing

- Thermal transfer & Direct thermal printing
- Issue mode: Batch / Cut / Strip
- Resolution: 12 dots/mm (305 dpi)
- Maximum effective print width:
213.3 mm (8.4 inches)
- Print length:
8 to 1364 mm (0.3 to 54 inches)
- Print Speed: Max 203 mm/sec (8"/sec)

Format

- Character Types:
Alphanumeric, symbols and special characters
- Bit map fonts:
20 fonts (Including EURO symbol)
- Outline fonts: 7 fonts (Including EURO symbol)
- Writable Character space:
Available. 2 byte characters (Japanese, Korean and Chinese characters) can be programmed as Writable characters.
- True Type Fonts:
True Type Fonts (1 byte) can be stored as optional fonts. TEC has 20 TrueType Fonts available as an option.
- Bar code Types :
UPC/EAN/JAN, Code39,
Code93, Code128,
CODABAR (NW7), ITF, MSI, EAN128
- 2-D code symbologies :
Datamatrix, Maxicode,
PDF (Micro+417), QR code, Post code,
Customer barcode
- Graphic:
TEC internal, BMP and PCX file formats can be used.

Paper

- Paper Width Range:
101.6 to 225.0 mm (4 to 8.85 inches)
including the backing paper
- Paper Length Range:
10 to 1368 mm (0.4 to 53.9 inches)
Standard
- Paper thickness:
TAG 0.1 to 0.17 mm (3.9 to 6.7 mils)
Label 0.13 to 0.17 mm (5.1 to 6.7 mils)

Ribbon

- Ribbon Width:
115 to 224 mm (4.5 to 8.8 inches)
- Maximum Ribbon length: 300m (984 feet)

Interface

- RS232C (D-SUB 25 PIN): Standard
- Centronics Interface: Standard
- Expansion I/O interface: Standard
- TCP/IP: Option
- PCMCIA: Option

Memory

- Internal memory: Flash memory 4MB
DRAM 16MB

Physical

- Height: 395 mm (15.5 inches)
- Width: 417mm (16.4 inches)
- Depth: 282mm (11.1 inches)
- Weight: 25Kg (39.6 lbs.)
(Without ribbon, paper, and paper holder)

Electrical

- Power:
100-120 VAC, 220-240 VAC, 50/60 Hz

Environmental

- 5 to 40 °C (41 to 104 °F)
- 25 ~ 85% Non-condensing relative humidity

Standard

- QP model: CE (CETECOM class A, TÜV/GS)
- QQ model: FCC class A, UL/CSA

Options

- B-4208-QM:
Cutter Module (Same as B-872)
- B-4908-H-QM:
Strip Module (Same as B-872)
- B-8700-PC-QM:
PCMCIA Module (Same as B-482)

- All company and/or product names are trademarks and/or registered trademarks of their respective owners.
- All features and specifications described on this brochure are subjected to change without notice.
- This paper is made of recycled paper.

TOSHIBA TEC CORPORATION

Retail Information Systems Company
INTERNATIONAL OPERATIONS
3-21-1 Nihonbashi Hamacho, Chuo-ku,
Tokyo 103-8482, JAPAN

<http://barcode.toshibatec.co.jp>

TEC America, Inc. Corporate Office

4401-A Bankers Circle
Atlanta, Georgia 30360, USA
Tel.: (770)449-3040
Fax: (770)449-1152

TEC Canada, Inc. Head Office

370 Britannia Road East, Unit #1
Mississauga, Ontario
L4Z 1X9, Canada
Tel.: (905)890-8283
Fax: (905)890-0082